


TECHNICAL INFORMATION

| | IMPERIAL | METRIC |
|--|--|---|
| Max Production Width | 102.36in | 2600mm |
| Total Thickness | 0.07in | 1.8mm |
| Mass | 0.45lb/ft ² | 2.2kg/m ² |
| Tensile force at 1% elongation (static) | 40lbf/in Internal Method - ref. ISO 21181 | 7N/mm |
| Working Temp. | +14/+158F ^o | -10/+70C ^o |
| Flexion (A) | 1.18in 30mm |  |
| Counter Flexion (B) | 1.57in 40mm | |

COEFFICIENT OF FRICTION (bottom side) - **Steel** 0.24

BEST USED FOR

General conveying, checkout belts

GENERAL CHARACTERISTICS

RECOMMENDED USES

Slider Bed | Flat Rollers | Slider Beds on Both Sides | Conveyor with Accumulation | Slide Bed with Pressure

SPECIAL CHARACTERISTICS

✓ Low Noise

BELT CONSTRUCTION INFORMATION

| TOP SIDE (Carrying) | | TENSION MEMBER | | BOTTOM SIDE (Pulley) | |
|----------------------------|------------------|-----------------|--|----------------------------|-------------|
| Material | PVC | Interply | PVC | Material | Fabric |
| Color | Black (B) | Weft | Rigid (R) | Color | Fabric (FA) |
| Thickness | 0.02in 0.4mm | Plies | 2 | Thickness | 0in 0mm |
| Hardness ISO 868 | 90 Shore A | Fabric | Light Rigid - Whisper Flexible (LR-FX) | Hardness ISO 868 | - |
| Surface | Matte Finish (A) | | | Surface | Bare (00) |

*Because of continuous development above data is subjected to change without prior notice by Sampla. This data replaces that included in previous publications. Sampla excludes any liability for the incorrect use of the above stated information.

