


NO60HC (SAM 055/A) FELTCON 1K/17 GR55 00/00 AS KG1GR5501

TECHNICAL INFORMATION

	IMPERIAL	METRIC
Max Production Width	78.74in	2000mm
Total Thickness	0.22in	5.5mm
Mass	0.72lb/ft ²	3.5kg/m ²
Tensile force at 1% elongation (static)	97lbf/in Internal Method - ref. ISO 21181	17N/mm
Working Temp.	+14/+248F ^o	-10/+120C ^o
Flexion (A)	4.72in 120mm	
Counter Flexion (B)	4.72in 120mm	

COEFFICIENT OF FRICTION (bottom side) - **Steel** 0.25

BEST USED FOR

GENERAL CHARACTERISTICS

5.5mm thick black needle polyester rubber impregnated antistatic

RECOMMENDED USES

Slider Bed | Flat Rollers | Slider Beds on Both Sides

SPECIAL CHARACTERISTICS

- ✓ **Antistatic**
ISO 284 & 21178
- ✓ **High Conductive**

BELT CONSTRUCTION INFORMATION

TOP SIDE (Carrying)		TENSION MEMBER	BOTTOM SIDE (Pulley)		
Material	Felt	Interply	-	Material	Felt
Color	Grey (GR)	Weft	Flexible (F)	Color	Grey (GR)
Thickness	0in 0mm	Plies	1	Thickness	0in 0mm
Hardness ISO 868	-	Fabric	Felt (K)	Hardness ISO 868	-
Surface	Bare (00)			Surface	Bare (00)

*Because of continuous development above data is subjected to change without prior notice by Sampla. This data replaces that included in previous publications. Sampla excludes any liability for the incorrect use of the above stated information.

RELEASED 01/01/2019