

SAMPLA CONVEYOR BELTS DATA SHEET

T20/E

PVCCON 2F-FX/12 B25 00/E AS

KA2BL2505

TECHNICAL INFORMATION

Max Production Width 62.99in 1600mm Total Thickness 0.1in 2.5mm Mass 0.53lb/ft² 2.6kg/m² Tensile force at 1% elongation (static) 68lbf/in 12N/mm Internal Method - ref. ISO 21181 Working Temp. +14/+158F° -10/+70C° Flexion (A) 1.97in 50mm A Counter Flexion (B) 2.76in 70mm B		IMPERIAL	METRIC	
Mass 0.53lb/ft² 2.6kg/m² Tensile force at 1% elongation (static) 68lbf/in 12N/mm Internal Method - ref. ISO 21181 Working Temp. +14/+158F° -10/+70C° Flexion (A) 1.97in 50mm A	Max Production Width	62.99in	1600mm	
Tensile force at 1% elongation (static) Working Temp. +14/+158F° -10/+70C° Flexion (A) 12N/mm Internal Method - ref. ISO 21181 -10/+70C° A	Total Thickness	0.1in	2.5mm	
1% elongation (static) Internal Method - ref. ISO 21181 Working Temp. +14/+158F° -10/+70C° Flexion (A) 1.97in 50mm	Mass	0.53lb/ft ²	2.6kg/m ²	
Working Temp. +14/+158F° -10/+70C° Flexion (A) 1.97in 50mm (A)	Tensile force at	68lbf/in	12N/mm	
Flexion (A) 1.97in 50mm (A)	1% elongation (static)	Internal Method - ref. ISO 21181		
0.70; 70	Working Temp.	+14/+158F ⁰	-10/+70C°	
Counter Flexion (B) 2.76in 70mm B	Flexion (A)	1.97in 50mm	A	
	Counter Flexion (B)	2.76in 70mm	B)	

COEFFICIENT OF FRICTION (bottom side) - **Steel** 0.24

BEST USED FOR

GENERAL CHARACTERISTICS

2 ply black PVC inverted oval. Whisper fabric. Antistatic.

RECOMMENDED USES

Slider Bed | Flat Rollers | Channel Trough | Incline Conveying | Slide Bed with Pressure | Bend Conveyor

SPECIAL CHARACTERISTICS



BELT CONSTRUCTION INFORMATION

TOP SIDE (Carrying)		TENSION MEMBER		BOTTOM SIDE (Pulley)	
Material	PVC	Interply	PVC	Material	Fabric
Color	Black (B)	Weft	Flexible (F)	Color	Fabric (FA)
Thickness	0.05in 1.15mm	Plies	2	Thickness	0in 0mm
Hardness ISO 868	85 Shore A	Fabric	Flexible - Whisper Flexible (F-FX)	Hardness ISO 868	-
Surface	Inverted Oval (E)		,	Surface	Bare (00)

^{*}Because of continuous development above data is subjected to change without prior notice by Sampla. This data replaces that included in previous publications. Sampla excludes any liability for the incorrect use of the above stated information.

RELEASED 01/01/2019

