


**U10**

**PVCCON 2LR/8 PG20 00/V05 AS**

**KA2PG2001**

**TECHNICAL INFORMATION**

	IMPERIAL	METRIC
<b>Max Production Width</b>	118.11in	3000mm
<b>Total Thickness</b>	0.08in	2mm
<b>Mass</b>	0.47lb/ft <sup>2</sup>	2.3kg/m <sup>2</sup>
<b>Tensile force at 1% elongation (static)</b>	46lb/in Internal Method - ref. ISO 21181	8N/mm
<b>Working Temp.</b>	+14/+158F <sup>o</sup>	-10/+70C <sup>o</sup>
<b>Flexion (A)</b>	1.18in 30mm	
<b>Counter Flexion (B)</b>	1.97in 50mm	

**COEFFICIENT OF FRICTION** (bottom side) - **Steel** 0.24

**BEST USED FOR**

**GENERAL CHARACTERISTICS**

2 ply green PVC antistatic. 2mm thick

**RECOMMENDED USES**

Slider Bed | Flat Rollers | Slide Bed with Pressure

**SPECIAL CHARACTERISTICS**

- ✓ **Antistatic**  
ISO 284 & 21178

**BELT CONSTRUCTION INFORMATION**



<b>TOP SIDE</b> (Carrying)		<b>TENSION MEMBER</b>		<b>BOTTOM SIDE</b> (Pulley)	
<b>Material</b>	PVC	<b>Interply</b>	PVC	<b>Material</b>	Fabric
<b>Color</b>	Petrol Green (PG)	<b>Weft</b>	Rigid (R)	<b>Color</b>	Fabric (FA)
<b>Thickness</b>	0.02in 0.5mm	<b>Plies</b>	2	<b>Thickness</b>	0in 0mm
<b>Hardness</b> ISO 868	74 Shore A	<b>Fabric</b>	Light Rigid (LR)	<b>Hardness</b> ISO 868	-
<b>Surface</b>	Smooth - Shiny (⌋)			<b>Surface</b>	Bare (00)

\*Because of continuous development above data is subjected to change without prior notice by Sampla. This data replaces that included in previous publications. Sampla excludes any liability for the incorrect use of the above stated information.

RELEASED 01/01/2019

