


TECHNICAL INFORMATION

	IMPERIAL	METRIC
Max Production Width	118.11in	3000mm
Total Thickness	0.05in	1.3mm
Mass	0.29lb/ft ²	1.4kg/m ²
Tensile force at 1% elongation (static)	46lbf/in Internal Method - ref. ISO 21181	8N/mm
Working Temp.	-13/+194F°	-25/+90C°
Flexion (A)	0.79in 20mm	
Counter Flexion (B)	1.18in 30mm	

COEFFICIENT OF FRICTION (bottom side) - **Steel** 0.2

BEST USED FOR

GENERAL CHARACTERISTICS

2 ply White PU glossy finish, antistatic and Food Approved

RECOMMENDED USES

Slider Bed | Flat Rollers

SPECIAL CHARACTERISTICS

- ✓ **Food Approved, FDA compliance**
 acc.to 21 CFR parts 170-19
- ✓ **Antistatic**
 ISO 284 & 21178
- ✓ **Oil & Fat Resistant**
- ✓ **Food Approved, EU compliance**
 (EC) No. 1935/2004 & (EU) No. 10/2011
- ✓ **Abrasion Resistant**

BELT CONSTRUCTION INFORMATION

TOP SIDE (Carrying)		TENSION MEMBER	BOTTOM SIDE (Pulley)		
Material	PU	Interply	PU	Material	Fabric
Color	White (W)	Weft	Rigid (R)	Color	Fabric (FA)
Thickness	0.01in 0.3mm	Plies	2	Thickness	0in 0mm
Hardness ISO 868	92 Shore A	Fabric	Light Rigid (LR)	Hardness ISO 868	-
Surface	Smooth - Shiny (L)			Surface	PU Impregnated (U0)

*Because of continuous development above data is subjected to change without prior notice by Sampla. This data replaces that included in previous publications. Sampla excludes any liability for the incorrect use of the above stated information.