


PN20/A

PUCON 2R/13 B23 00/U05A AR

KD2BL2301

TECHNICAL INFORMATION

	IMPERIAL	METRIC
Max Production Width	125.98in	3200mm
Total Thickness	0.09in	2.3mm
Mass	0.55lb/ft ²	2.7kg/m ²
Tensile force at 1% elongation (static)	74lb/in	13N/mm
	Internal Method - ref. ISO 21181	
Working Temp.	-13/+194F ^o	-25/+90C ^o
Flexion (A)	3.15in 80mm	
Counter Flexion (B)	5.12in 130mm	

COEFFICIENT OF FRICTION (bottom side) - **Steel** 0.2

BEST USED FOR

GENERAL CHARACTERISTICS

2 ply black PU, abrasion resistant

RECOMMENDED USES

Slider Bed | Flat Rollers | Conveyor with Accumulation | Slide Bed with Pressure

SPECIAL CHARACTERISTICS

✓ Abrasion Resistant

✓ Oil & Fat Resistant

BELT CONSTRUCTION INFORMATION



TOP SIDE (Carrying)		TENSION MEMBER		BOTTOM SIDE (Pulley)	
Material	PU	Interply	PU	Material	Fabric
Color	Black (B)	Weft	Rigid (R)	Color	Fabric (FA)
Thickness	0.02in 0.4mm	Plies	2	Thickness	0in 0mm
Hardness ISO 868	92 Shore A	Fabric	Rigid (R)	Hardness ISO 868	-
Surface	Matte Finish (A)			Surface	PU Impregnated (U0)

*Because of continuous development above data is subjected to change without prior notice by Sampla. This data replaces that included in previous publications. Sampla excludes any liability for the incorrect use of the above stated information.

RELEASED 01/01/2019