


B21

FABCON 2F/12 PG20 U0/U0

KC2PG2001

TECHNICAL INFORMATION

| | IMPERIAL | METRIC |
|--|--|---|
| Max Production Width | 118.11in | 3000mm |
| Total Thickness | 0.08in | 2mm |
| Mass | 0.47lb/ft ² | 2.3kg/m ² |
| Tensile force at 1% elongation (static) | 68lbf/in Internal Method - ref. ISO 21181 | 12N/mm |
| Working Temp. | +14/+158F ^o | -10/+70C ^o |
| Flexion (A) | 1.18in 30mm |  |
| Counter Flexion (B) | 1.18in 30mm | |

COEFFICIENT OF FRICTION (bottom side) - **Steel** 0.2

BEST USED FOR

GENERAL CHARACTERISTICS

RECOMMENDED USES

Slider Bed | Flat Rollers | Slider Beds on Both Sides | Channel Trough | Conventional Trough | Bucket Elevator | Conveyor with Accumulation | Slide Bed with Pressure | Bend Conveyor

SPECIAL CHARACTERISTICS

BELT CONSTRUCTION INFORMATION

| TOP SIDE (Carrying) | | TENSION MEMBER | | BOTTOM SIDE (Pulley) | |
|----------------------------|---------------------|-----------------|--------------|----------------------------|---------------------|
| Material | Fabric | Interply | PVC | Material | Fabric |
| Color | Petrol Green (PG) | Weft | Flexible (F) | Color | Petrol Green (PG) |
| Thickness | 0in 0mm | Plies | 2 | Thickness | 0in 0mm |
| Hardness ISO 868 | - | Fabric | Flexible (F) | Hardness ISO 868 | - |
| Surface | PU Impregnated (U0) | | | Surface | PU Impregnated (U0) |

*Because of continuous development above data is subjected to change without prior notice by Sampla. This data replaces that included in previous publications. Sampla excludes any liability for the incorrect use of the above stated information.

RELEASED 01/01/2019