




B30/AG

FABCON 3R/15 AG35 V0/U0

KC3AG3502

TECHNICAL INFORMATION

	IMPERIAL	METRIC
Max Production Width	118.11in	3000mm
Total Thickness	0.14in	3.5mm
Mass	0.82lb/ft ²	4kg/m ²
Tensile force at 1% elongation (static)	86lbf/in Internal Method - ref. ISO 21181	15N/mm
Working Temp.	+14/+194F ^o	-10/+90C ^o
Flexion (A)	3.54in 90mm	
Counter Flexion (B)	3.54in 90mm	

COEFFICIENT OF FRICTION (bottom side) - **Steel** 0.2

BEST USED FOR

GENERAL CHARACTERISTICS

3 ply bare by bare PVC apple green

RECOMMENDED USES

Slider Bed | Flat Rollers | Slider Beds on Both Sides | Conveyor with Accumulation | Slide Bed with Pressure

SPECIAL CHARACTERISTICS

BELT CONSTRUCTION INFORMATION

TOP SIDE (Carrying)		TENSION MEMBER		BOTTOM SIDE (Pulley)	
Material	Fabric	Interply	PVC	Material	Fabric
Color	Apple Green (AG)	Weft	Rigid (R)	Color	Apple Green (AG)
Thickness	0in 0mm	Plies	3	Thickness	0in 0mm
Hardness ISO 868	-	Fabric	Rigid (R)	Hardness ISO 868	-
Surface	PU Impregnated (U0)			Surface	PVC Impregnated (V0)

*Because of continuous development above data is subjected to change without prior notice by Sampla. This data replaces that included in previous publications. Sampla excludes any liability for the incorrect use of the above stated information.

RELEASED 01/01/2019

