




F20 **PVCEXCON 2R/12 W26 U0/V08 FA** **KB2WH2604**

TECHNICAL INFORMATION

	IMPERIAL	METRIC
Max Production Width	118.11in	3000mm
Total Thickness	0.1in	2.6mm
Mass	0.62lb/ft ²	3kg/m ²
Tensile force at 1% elongation (static)	68lb/in Internal Method - ref. ISO 21181	12N/mm
Working Temp.	+14/+158F ^o	-10/+70C ^o
Flexion (A)	1.97in 50mm	
Counter Flexion (B)	2.36in 60mm	

COEFFICIENT OF FRICTION (bottom side) - **Steel** 0.2

BEST USED FOR

GENERAL CHARACTERISTICS

2 ply white PVC Food approved 2.6mm thick


RECOMMENDED USES

Slider Bed | Flat Rollers | Slide Bed with Pressure

SPECIAL CHARACTERISTICS

- ✓ **Food Approved, FDA compliance**
acc.to 21 CFR parts 170-19
- ✓ **Food Approved, EU compliance**
(EC) No. 1935/2004 & (EU) No. 10/2011
- ✓ **Oil & Fat Resistant**

BELT CONSTRUCTION INFORMATION



TOP SIDE (Carrying)		TENSION MEMBER		BOTTOM SIDE (Pulley)	
Material	PVC	Interply	PVC	Material	Fabric
Color	White (W)	Weft	Rigid (R)	Color	Fabric (FA)
Thickness	0.03in 0.8mm	Plies	2	Thickness	0in 0mm
Hardness ISO 868	72 Shore A	Fabric	Rigid (R)	Hardness ISO 868	0 Shore A
Surface	Smooth - Shiny (┘)			Surface	PU Impregnated (U0)

*Because of continuous development above data is subjected to change without prior notice by Sampla. This data replaces that included in previous publications. Sampla excludes any liability for the incorrect use of the above stated information.

RELEASED 01/01/2019