




F20/T

PVCEXCON 2R/12 W50 U0/T FA

KB2WH5002

TECHNICAL INFORMATION

	IMPERIAL	METRIC
Max Production Width	118.11in	3000mm
Total Thickness	0.2in	5mm
Mass	0.96lb/ft ²	4.7kg/m ²
Tensile force at 1% elongation (static)	68lb/in Internal Method - ref. ISO 21181	12N/mm
Working Temp.	+14/+158F ^o	-10/+70C ^o
Flexion (A)	3.15in 80mm	
Counter Flexion (B)	4.33in 110mm	

COEFFICIENT OF FRICTION (bottom side) - **Steel** 0.2

BEST USED FOR

GENERAL CHARACTERISTICS

2 ply white PVC sawtooth. Food approved

RECOMMENDED USES

Slider Bed | Flat Rollers | Incline Conveying |
 Incline Variation | Slide Bed with Pressure

SPECIAL CHARACTERISTICS

✓ **Food Approved, FDA compliance**
 acc.to 21 CFR parts 170-19

✓ **Oil & Fat Resistant**

✓ **Food Approved, EU compliance**
 (EC) No. 1935/2004 & (EU) No. 10/2011

BELT CONSTRUCTION INFORMATION



TOP SIDE (Carrying)		TENSION MEMBER		BOTTOM SIDE (Pulley)	
Material	PVC	Interply	PVC	Material	Fabric
Color	White (W)	Weft	Rigid (R)	Color	Fabric (FA)
Thickness	0.13in 3.3mm	Plies	2	Thickness	0in 0mm
Hardness ISO 868	65 Shore A	Fabric	Rigid (R)	Hardness ISO 868	-
Surface	Saw Tooth (T)			Surface	PU Impregnated (U0)

*Because of continuous development above data is subjected to change without prior notice by Sampla. This data replaces that included in previous publications. Sampla excludes any liability for the incorrect use of the above stated information.

RELEASED 08/11/2021