




**L10/Y**

**PVCCON 2LR/8 GR28 00/Y**

**KA2GR2801**

**TECHNICAL INFORMATION**

	IMPERIAL	METRIC
<b>Max Production Width</b>	118.11in	3000mm
<b>Total Thickness</b>	0.11in	2.8mm
<b>Mass</b>	0.57lb/ft <sup>2</sup>	2.8kg/m <sup>2</sup>
<b>Tensile force at 1% elongation (static)</b>	46lbf/in Internal Method - ref. ISO 21181	8N/mm
<b>Working Temp.</b>	+14/+158F <sup>o</sup>	-10/+70C <sup>o</sup>
<b>Flexion (A)</b>	1.57in 40mm	
<b>Counter Flexion (B)</b>	2.36in 60mm	

**COEFFICIENT OF FRICTION** (bottom side) - **Steel** 0.24

**BEST USED FOR**

**GENERAL CHARACTERISTICS**

2 ply grey PVC, Y profile top cover.

**RECOMMENDED USES**

Slider Bed | Flat Rollers | Incline Conveying |  
 Incline Variation | Slide Bed with Pressure

**SPECIAL CHARACTERISTICS**

**BELT CONSTRUCTION INFORMATION**



<b>TOP SIDE</b> (Carrying)		<b>TENSION MEMBER</b>		<b>BOTTOM SIDE</b> (Pulley)	
<b>Material</b>	PVC	<b>Interply</b>	PVC	<b>Material</b>	Fabric
<b>Color</b>	Grey (GR)	<b>Weft</b>	Rigid (R)	<b>Color</b>	Fabric (FA)
<b>Thickness</b>	0.05in 1.3mm	<b>Plies</b>	2	<b>Thickness</b>	0in 0mm
<b>Hardness</b> ISO 868	46 Shore A	<b>Fabric</b>	Light Rigid (LR)	<b>Hardness</b> ISO 868	-
<b>Surface</b>	Y Structure (Y)			<b>Surface</b>	Bare (00)

\*Because of continuous development above data is subjected to change without prior notice by Sampla. This data replaces that included in previous publications. Sampla excludes any liability for the incorrect use of the above stated information.

RELEASED 01/01/2019