


TECHNICAL INFORMATION

	IMPERIAL	METRIC
Max Production Width	118.11in	3000mm
Total Thickness	0.08in	2.1mm
Mass	0.53lb/ft ²	2.6kg/m ²
Tensile force at 1% elongation (static)	80lb/in Internal Method - ref. ISO 21181	14N/mm
Working Temp.	+14/+158F ^o	-10/+70C ^o
Flexion (A)	1.97in 50mm	
Counter Flexion (B)	2.36in 60mm	

COEFFICIENT OF FRICTION (bottom side) - **Steel** 0.24

BEST USED FOR

GENERAL CHARACTERISTICS

2 ply black PVC fire retardant

RECOMMENDED USES

Slider Bed | Flat Rollers | Slide Bed with Pressure

SPECIAL CHARACTERISTICS

- ✓ **Antistatic**
ISO 284 & 21178
- ✓ **Low Noise**
- ✓ **Flame Retardant**
ISO 284 & 21178

BELT CONSTRUCTION INFORMATION

TOP SIDE (Carrying)		TENSION MEMBER		BOTTOM SIDE (Pulley)	
Material	PVC	Interply	PVC	Material	Fabric
Color	Black (B)	Weft	Rigid (R)	Color	Fabric (FA)
Thickness	0.02in 0.5mm	Plies	2	Thickness	0in 0mm
Hardness ISO 868	85 Shore A	Fabric	Rigid - Rigid Whisper (R-RX)	Hardness ISO 868	-
Surface	Matte Finish (A)			Surface	Bare (00)

*Because of continuous development above data is subjected to change without prior notice by Sampla. This data replaces that included in previous publications. Sampla excludes any liability for the incorrect use of the above stated information.