


**N20/LG**

**PVCCON 2R-RX/14 B30 00/LG AS FR**

**KA2BL3001**

**TECHNICAL INFORMATION**

	IMPERIAL	METRIC
<b>Max Production Width</b>	118.11in	3000mm
<b>Total Thickness</b>	0.12in	3mm
<b>Mass</b>	0.66lb/ft <sup>2</sup>	3.2kg/m <sup>2</sup>
<b>Tensile force at 1% elongation (static)</b>	80lb/in Internal Method - ref. ISO 21181	14N/mm
<b>Working Temp.</b>	+14/+158F <sup>0</sup>	-10/+70C <sup>0</sup>
<b>Flexion (A)</b>	1.38in 35mm	
<b>Counter Flexion (B)</b>	1.97in 50mm	

**COEFFICIENT OF FRICTION** (bottom side) - **Steel** 0.24

**BEST USED FOR**

**GENERAL CHARACTERISTICS**

2 ply black PVC with longitudinal groove top. Antistatic, fire retardant and whisper weave fabric.

**RECOMMENDED USES**

Slider Bed | Flat Rollers | Incline Conveying | Incline Variation | Slide Bed with Pressure

**SPECIAL CHARACTERISTICS**

- ✓ **Antistatic**  
ISO 284 & 21178
- ✓ **Low Noise**
- ✓ **Flame Retardant**  
ISO 284 & 21178

**BELT CONSTRUCTION INFORMATION**

TOP SIDE (Carrying)		TENSION MEMBER	BOTTOM SIDE (Pulley)		
<b>Material</b>	PVC	<b>Interply</b>	PVC	<b>Material</b>	Fabric
<b>Color</b>	Black (B)	<b>Weft</b>	Rigid (R)	<b>Color</b>	Fabric (FA)
<b>Thickness</b>	0.04in 1.1mm	<b>Plies</b>	2	<b>Thickness</b>	0in 0mm
<b>Hardness</b> ISO 868	40 Shore A	<b>Fabric</b>	Rigid - Rigid Whisper (R-RX)	<b>Hardness</b> ISO 868	-
<b>Surface</b>	Longitudinal Groove (LG)			<b>Surface</b>	Bare (00)

\*Because of continuous development above data is subjected to change without prior notice by Sampla. This data replaces that included in previous publications. Sampla excludes any liability for the incorrect use of the above stated information.

RELEASED 01/01/2019

