


**P19/B**

**PUCON 2R/8 W24 U0/B FA AR**

**KD2WH2301**

**TECHNICAL INFORMATION**

	IMPERIAL	METRIC
<b>Max Production Width</b>	118.11in	3000mm
<b>Total Thickness</b>	0.09in	2.4mm
<b>Mass</b>	0.47lb/ft <sup>2</sup>	2.3kg/m <sup>2</sup>
<b>Tensile force at 1% elongation (static)</b>	46lb/in Internal Method - ref. ISO 21181	8N/mm
<b>Working Temp.</b>	-13/+194F <sup>o</sup>	-25/+90C <sup>o</sup>
<b>Flexion (A)</b>	2.76in 70mm	
<b>Counter Flexion (B)</b>	3.54in 90mm	

**COEFFICIENT OF FRICTION** (bottom side) - **Steel** 0.2

**BEST USED FOR**

**GENERAL CHARACTERISTICS**

2 ply white PU, mini rough top surface, Food Approved

**RECOMMENDED USES**

Slider Bed | Flat Rollers | Channel Trough | Incline Conveying | Incline Variation | Slide Bed with Pressure

**SPECIAL CHARACTERISTICS**

✓ **Food Approved, FDA compliance**  
 acc.to 21 CFR parts 170-19

✓ **Food Approved, EU compliance**  
 (EC) No. 1935/2004 & (EU) No. 10/2011

✓ **Abrasion Resistant**

✓ **Oil & Fat Resistant**

**BELT CONSTRUCTION INFORMATION**



<b>TOP SIDE</b> (Carrying)		<b>TENSION MEMBER</b>		<b>BOTTOM SIDE</b> (Pulley)	
<b>Material</b>	PU	<b>Interply</b>	PU	<b>Material</b>	Fabric
<b>Color</b>	White (W)	<b>Weft</b>	Rigid (R)	<b>Color</b>	Fabric (FA)
<b>Thickness</b>	0.04in 1.1mm	<b>Plies</b>	2	<b>Thickness</b>	0in 0mm
<b>Hardness</b> ISO 868	88 Shore A	<b>Fabric</b>	Light Rigid (LR)	<b>Hardness</b> ISO 868	-
<b>Surface</b>	Mini Rough Top (B)			<b>Surface</b>	PU Impregnated (U0)

\*Because of continuous development above data is subjected to change without prior notice by Sampla. This data replaces that included in previous publications. Sampla excludes any liability for the incorrect use of the above stated information.

RELEASED 01/01/2019