


TECHNICAL INFORMATION

	IMPERIAL	METRIC
Max Production Width	118.11in	3000mm
Total Thickness	0.11in	2.8mm
Mass	0.53lb/ft ²	2.6kg/m ²
Tensile force at 1% elongation (static)	74lb/in Internal Method - ref. ISO 21181	13N/mm
Working Temp.	-13/+194F ^o	-25/+90C ^o
Flexion (A)	3.15in 80mm	
Counter Flexion (B)	3.94in 100mm	

COEFFICIENT OF FRICTION (bottom side) - **Steel** 0.2

BEST USED FOR

GENERAL CHARACTERISTICS

2 ply white PU mini rough top cover, Food Approved and antistatic

RECOMMENDED USES

Slider Bed | Flat Rollers | Incline Conveying | Incline Variation | Slide Bed with Pressure

SPECIAL CHARACTERISTICS

- ✓ **Food Approved, FDA compliance**
acc.to 21 CFR parts 170-19
- ✓ **Antistatic**
ISO 284 & 21178
- ✓ **Oil & Fat Resistant**
- ✓ **Food Approved, EU compliance**
(EC) No. 1935/2004 & (EU) No. 10/2011
- ✓ **Abrasion Resistant**

BELT CONSTRUCTION INFORMATION

TOP SIDE (Carrying)		TENSION MEMBER		BOTTOM SIDE (Pulley)	
Material	PU	Interply	PU	Material	Fabric
Color	White (W)	Weft	Rigid (R)	Color	Fabric (FA)
Thickness	0.04in 1mm	Plies	2	Thickness	0in 0mm
Hardness ISO 868	92 Shore A	Fabric	Rigid (R)	Hardness ISO 868	-
Surface	Mini Rough Top (B)			Surface	PU Impregnated (U0)

*Because of continuous development above data is subjected to change without prior notice by Sampla. This data replaces that included in previous publications. Sampla excludes any liability for the incorrect use of the above stated information.