


P7/Z

PUCON 1RR/7 W15 U0/Z AS FA

KD1WH1501

TECHNICAL INFORMATION

| | IMPERIAL | METRIC |
|--|---|---|
| Max Production Width | 122.05in | 3100mm |
| Total Thickness | 0.06in | 1.5mm |
| Mass | 0.27lb/ft ² | 1.3kg/m ² |
| Tensile force at 1% elongation (static) | 40lb/in Internal Method - ref. ISO 21181 | 7N/mm |
| Working Temp. | -13/+194F ^o | -25/+90C ^o |
| Flexion (A) | 0.39in 10mm |  |
| Counter Flexion (B) | 1.18in 30mm | |

COEFFICIENT OF FRICTION (bottom side) - **Steel** 0.2

BEST USED FOR

GENERAL CHARACTERISTICS

1 ply white PU negative pyramid.. Food approved

RECOMMENDED USES

Slider Bed | Flat Rollers | Incline Conveying | Incline Variation | Slide Bed with Pressure | Bend Conveyor | Knife Edge Conveyor

SPECIAL CHARACTERISTICS

✓ **Food Approved, FDA compliance**
 acc.to 21 CFR parts 170-19

✓ **Food Approved, EU compliance**
 (EC) No. 1935/2004 & (EU) No. 10/2011

✓ **Antistatic**
 ISO 284 & 21178

✓ **Abrasion Resistant**

✓ **Oil & Fat Resistant**

BELT CONSTRUCTION INFORMATION



| TOP SIDE (Carrying) | | TENSION MEMBER | | BOTTOM SIDE (Pulley) | |
|----------------------------|----------------------|-----------------------|------------------|-----------------------------|---------------------|
| Material | PU | Interply | - | Material | Fabric |
| Color | White (W) | Weft | Rigid (R) | Color | Fabric (FA) |
| Thickness | 0.03in 0.7mm | Plies | 1 | Thickness | 0in 0mm |
| Hardness ISO 868 | 88 Shore A | Fabric | Extra Rigid (RR) | Hardness ISO 868 | - |
| Surface | Negative Pyramid (Z) | | | Surface | PU Impregnated (U0) |

*Because of continuous development above data is subjected to change without prior notice by Sampla. This data replaces that included in previous publications. Sampla excludes any liability for the incorrect use of the above stated information.

RELEASED 01/01/2019