




PV24/A

PUCON 2R-RX/14 DG40 U0/U20A AS AR FA

KD2DG4002

TECHNICAL INFORMATION

	IMPERIAL	METRIC
Max Production Width	118.11in	3000mm
Total Thickness	0.16in	4mm
Mass	0.98lb/ft ²	4.8kg/m ²
Tensile force at 1% elongation (static)	80lbf/in Internal Method - ref. ISO 21181	14N/mm
Working Temp.	-13/+194F ^o	-25/+90C ^o
Flexion (A)	3.94in 100mm	
Counter Flexion (B)	5.51in 140mm	

COEFFICIENT OF FRICTION (bottom side) - **Steel** 0.2

BEST USED FOR

Metal cutting, recycling, wood industry

GENERAL CHARACTERISTICS

2 ply green PU, 2mm thick cover. FDA, antistatic and abrasion resistant

RECOMMENDED USES

Slider Bed | Flat Rollers | Conveyor with Accumulation | Slide Bed with Pressure

SPECIAL CHARACTERISTICS

✓ **Food Approved, FDA compliance**
 acc.to 21 CFR parts 170-19

✓ **Antistatic**
 ISO 284 & 21178

✓ **Low Noise**

✓ **Food Approved, EU compliance**
 (EC) No. 1935/2004 & (EU) No. 10/2011

✓ **Abrasion Resistant**

✓ **Oil & Fat Resistant**

BELT CONSTRUCTION INFORMATION

TOP SIDE (Carrying)		TENSION MEMBER		BOTTOM SIDE (Pulley)	
Material	PU	Interply	PU	Material	Fabric
Color	Dark Green (DG)	Weft	Rigid (R)	Color	Fabric
Thickness	0.08in 2mm	Plies	2	Thickness	- 0mm
Hardness ISO 868	88 Shore A	Fabric	Rigid - Rigid Whisper (R-RX)	Hardness ISO 868	-
Surface	Matte Finish (A)			Surface	PU Impregnated (U0)

*Because of continuous development above data is subjected to change without prior notice by Sampla. This data replaces that included in previous publications. Sampla excludes any liability for the incorrect use of the above stated information.

RELEASED 01/01/2019