


**R13/DB**

**FABCON 2LR/6 DB10 U0/U0 AS FA**

**KC2DB1001**

**TECHNICAL INFORMATION**

|  | IMPERIAL                                     | METRIC  |
|--|--|---|
| <b>Max Production Width</b>                    | 125.98in                                     | 3200mm  |
| <b>Total Thickness</b>                         | 0.04in                                       | 1mm   |
| <b>Mass</b>                                    | 0.23lb/ft <sup>2</sup>                       | 1.1kg/m <sup>2</sup>  |
| <b>Tensile force at 1% elongation (static)</b> | 34lbf/in<br>Internal Method - ref. ISO 21181 | 6N/mm   |
| <b>Working Temp.</b>                           | -13/+194F <sup>o</sup>                       | -25/+90C <sup>o</sup>   |
| <b>Flexion (A)</b>                             | 0.39in 10mm                                  |  |
| <b>Counter Flexion (B)</b>                     | 0.79in 20mm                                  |   |

**COEFFICIENT OF FRICTION** (bottom side) - **Steel** 0.2

**BEST USED FOR**

**GENERAL CHARACTERISTICS**

2 ply bare by bare PU, blue. Food approved, antistatic.

**RECOMMENDED USES**

Slider Bed | Flat Rollers | Slider Beds on Both Sides | Conveyor with Accumulation | Slide Bed with Pressure

**SPECIAL CHARACTERISTICS**

✓ **Food Approved, FDA compliance**  
 acc.to 21 CFR parts 170-19

✓ **Antistatic**  
 ISO 284 & 21178

✓ **Food Approved, EU compliance**  
 (EC) No. 1935/2004 & (EU) No. 10/2011

**BELT CONSTRUCTION INFORMATION**



| <b>TOP SIDE</b> (Carrying) |                     | <b>TENSION MEMBER</b> |                  | <b>BOTTOM SIDE</b> (Pulley) |                     |
|----------------------------|---------------------|-----------------------|------------------|-----------------------------|---------------------|
| <b>Material</b>            | Fabric              | <b>Interply</b>       | PU               | <b>Material</b>             | Fabric              |
| <b>Color</b>               | Dark Blue (DB)      | <b>Weft</b>           | Rigid (R)        | <b>Color</b>                | Dark Blue (DB)      |
| <b>Thickness</b>           | 0in 0mm             | <b>Plies</b>          | 2                | <b>Thickness</b>            | 0in 0mm             |
| <b>Hardness</b><br>ISO 868 | -                   | <b>Fabric</b>         | Light Rigid (LR) | <b>Hardness</b><br>ISO 868  | -                   |
| <b>Surface</b>             | PU Impregnated (U0) |                       |                  | <b>Surface</b>              | PU Impregnated (U0) |

\*Because of continuous development above data is subjected to change without prior notice by Sampla. This data replaces that included in previous publications. Sampla excludes any liability for the incorrect use of the above stated information.

RELEASED 01/01/2019