




T20/P

PVCCON 2F-FX/12 B30 00/P AS

KA2BL3002

TECHNICAL INFORMATION

	IMPERIAL	METRIC
Max Production Width	80.71in	2050mm
Total Thickness	0.12in	3mm
Mass	0.68lb/ft ²	3.3kg/m ²
Tensile force at 1% elongation (static)	68lb/in Internal Method - ref. ISO 21181	12N/mm
Working Temp.	+14/+158F ^o	-10/+70C ^o
Flexion (A)	2.36in 60mm	
Counter Flexion (B)	3.15in 80mm	

COEFFICIENT OF FRICTION (bottom side) - **Steel** 0.24

BEST USED FOR

GENERAL CHARACTERISTICS

2 ply black PVC, way low rough top cover. Whisper fabric and antistatic.

RECOMMENDED USES

Slider Bed | Flat Rollers | Channel Trough | Incline Conveying | Slide Bed with Pressure | Bend Conveyor

SPECIAL CHARACTERISTICS

- ✓ **Antistatic**
ISO 284 & 21178
- ✓ **Low Noise**

BELT CONSTRUCTION INFORMATION



TOP SIDE (Carrying)		TENSION MEMBER		BOTTOM SIDE (Pulley)	
Material	PVC	Interply	PVC	Material	Fabric
Color	Black (B)	Weft	Flexible (F)	Color	Fabric (FA)
Thickness	0.07in 1.65mm	Plies	2	Thickness	0in 0mm
Hardness ISO 868	85 Shore A	Fabric	Flexible - Whisper Flexible (F-FX)	Hardness	- ISO 868
Surface	Low Super Grip (P)			Surface	Bare (00)

*Because of continuous development above data is subjected to change without prior notice by Sampla. This data replaces that included in previous publications. Sampla excludes any liability for the incorrect use of the above stated information.

RELEASED 01/01/2019