


U14/AG

PVCCON 2R/12 AG20 00/V05 AS

KA2AG2002

TECHNICAL INFORMATION

	IMPERIAL	METRIC
Max Production Width	118.11in	3000mm
Total Thickness	0.08in	2mm
Mass	0.53lb/ft ²	2.6kg/m ²
Tensile force at 1% elongation (static)	68lb/in	12N/mm
	Internal Method - ref. ISO 21181	
Working Temp.	+14/+158F ^o	-10/+70C ^o
Flexion (A)	1.57in 40mm	
Counter Flexion (B)	2.36in 60mm	

COEFFICIENT OF FRICTION (bottom side) - **Steel** 0.24

BEST USED FOR

GENERAL CHARACTERISTICS

2 ply apple green PVC antistatic


RECOMMENDED USES

Slider Bed | Flat Rollers | Slide Bed with Pressure

SPECIAL CHARACTERISTICS

- ✓ **Antistatic**
ISO 284 & 21178

BELT CONSTRUCTION INFORMATION



TOP SIDE (Carrying)		TENSION MEMBER		BOTTOM SIDE (Pulley)	
Material	PVC	Interply	PVC	Material	Fabric
Color	Apple Green (AG)	Weft	Rigid (R)	Color	Fabric (FA)
Thickness	0.02in 0.5mm	Plies	2	Thickness	0in 0mm
Hardness ISO 868	74 Shore A	Fabric	Rigid (R)	Hardness ISO 868	-
Surface	Smooth - Shiny (⌋)			Surface	Bare (00)

*Because of continuous development above data is subjected to change without prior notice by Sampla. This data replaces that included in previous publications. Sampla excludes any liability for the incorrect use of the above stated information.

RELEASED 01/01/2019