




U6

PVCCON 1LR/5 PG13 00/V08 AS

KA1PG1301

TECHNICAL INFORMATION

	IMPERIAL	METRIC
Max Production Width	118.11in	3000mm
Total Thickness	0.05in	1.3mm
Mass	0.29lb/ft ²	1.4kg/m ²
Tensile force at 1% elongation (static)	29lbf/in Internal Method - ref. ISO 21181	5N/mm
Working Temp.	+14/+158F ^o	-10/+70C ^o
Flexion (A)	0.79in 20mm	
Counter Flexion (B)	1.18in 30mm	

COEFFICIENT OF FRICTION (bottom side) - **Steel** 0.24

BEST USED FOR

GENERAL CHARACTERISTICS

1 ply green PVC. Antistatic

RECOMMENDED USES

Slider Bed | Flat Rollers | Slide Bed with Pressure | Knife Edge Conveyor

SPECIAL CHARACTERISTICS

- ✓ **Antistatic**
ISO 284 & 21178

BELT CONSTRUCTION INFORMATION



TOP SIDE (Carrying)		TENSION MEMBER		BOTTOM SIDE (Pulley)	
Material	PVC	Interply	PVC	Material	Fabric
Color	Petrol Green (PG)	Weft	Rigid (R)	Color	Fabric (FA)
Thickness	0.03in 0.8mm	Plies	1	Thickness	0in 0mm
Hardness ISO 868	74 Shore A	Fabric	Light Rigid (LR)	Hardness ISO 868	-
Surface	Smooth - Shiny (⌋)			Surface	Bare (00)

*Because of continuous development above data is subjected to change without prior notice by Sampla. This data replaces that included in previous publications. Sampla excludes any liability for the incorrect use of the above stated information.

RELEASED 01/01/2019